



Date: 3 december 2006

<b>Provider</b>	<b>XeloQ</b>
<b>Website</b>	xeloq.com
<b>Holder</b>	
<b>Country</b>	NL
<b>Registration of SIP-Link</b>	√
<b>Outgoing calls (National / International)</b>	√ / √
<b>Incoming calls (National / International)</b>	√ / √
<b>Correct CLIP (National / International)</b>	- / -
<b>Can be set on hold</b>	√
<b>CLIR Number Suppression</b>	-
<b>CLIP No Screening</b>	-
<b>Secure RTP / TLS</b>	- / -
<b>Fax T.38 (Incoming / Outgoing)</b>	- / -
<b>DDI-Support (without registration)</b>	-
<b>DDI-Support (with registration)</b>	-
<b>Correct DDI CLIP (National / International)</b>	- / -
<b>DTMF (out-of-band) using SIP INFO</b>	-
<b>DTMF (out-of-band) conforming RFC 2833</b>	-
<b>DTMF (in-band) toward PSTN</b>	√
<b>G.711a / G.711u / G.729</b>	- / - / √
<b>G.723 / G.726 / GSM / Speex / iLBC</b>	√ / - / √ / - / -
<b>SIP Proxy Software</b>	GNC Softswitch
<b>Working since SwyxWare version</b>	6.01 MP1

**Comments XeloQ:**

DDI numbers work OK with Swyx because it is treated as an inbound VoIP call.

Also incoming CLID's are passed-through in our system.