

Configuration Cisco Call Manager Express on XeloQ Platform (CCME v3.3 en hoger)

Below you will find a working configuration of an existing Cisco Call Manager Express.
XeloQ does not deliver support for Cisco Call Manager Express.

If you would like to make use of Cisco expertise, we can introduce you at one of our Cisco partners.

```
-----  
  
!example config for outgoing calls via goandcall.com (XeloQ)  
!replace 700000 in this configuration with right endpoint (your SIP account)  
!=====
```

```
!  
!  
!-----  
!  
sip-ua  
authentication username 700000 password  
realm sip.goandcall.com  
retry register 3  
registrar dns:sip.goandcall.com:6060 expires 3600  
!  
!-----  
!  
!translate outgoing calling-number to SIP-endpoint#  
!  
voice translation-rule 1  
rule 1 /^.* /700000/ type any unknown  
!  
voice translation-profile xeloq-out  
translate calling 1  
!  
!-----  
!  
!general dialpeer for outgoing calls via goandcall.com  
!  
dial-peer voice 1 voip  
description outgoing dial-peer via goandcall.com  
destination-pattern 0.T  
session protocol sipv2  
session target dns:sip.goandcall.com:6060  
no vad
```

NOTE:

This information came from another customer; we do not have this device in our LAB (so we can not give any warranties it works on your environment) but it seems it can work fine.

DISCLAIMER:

Aan informatie op deze pagina kunnen geen rechten worden verleend t.a.v. beschikbaarheid of prijzen van bepaalde diensten. Prijzen, verstrekking van informatie en voorwaarden genoemd op deze pagina zijn 'onder voorbehoud'.