

Configuration LinkSys SPA-941 on XeloQ Communications / Goandcall.com

SIPURA
technology, inc.

Sipura Telephone Configuration

Info **System** SIP Provisioning Regional Phone Ext 1 Ext 2 User Sipura Technology Inc [User Login](#) [basic](#) | [advanced](#)
[Personal Directory](#) [Call History](#)

System Configuration

Restricted Access Domains:

Enable Web Server: Web Server Port:

Enable Web Admin Access: Admin Passwd:

User Password:

Internet Connection Type

DHCP:

Static IP: NetMask:

Gateway:

Optional Network Configuration

HostName: Domain:

Primary DNS: Secondary DNS:

DNS Server Order: DNS Query Mode:

Syslog Server: Debug Server:

Debug Level: Primary NTP Server:

Secondary NTP Server:

VLAN Settings

Enable VLAN: VLAN ID:

[User Login](#) [basic](#) | [advanced](#)

Copyright © 2003-2005 Sipura Technology. All Rights Reserved.

http://www.sipura.com/ Internet

DNS 1: use 81.26.212.151 (is a goandcall.com DNS server; use only if normal DNS is not accurate)

Sipura SPA Configuration - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Search Favorites

Address http://192.168.1.65/admin/advanced Go Links

Info System **SIP** Provisioning Regional Phone Ext 1 Ext 2 User

User Login basic | advanced
Personal Directory Call History

SIP Parameters

Max Forward:	70	Max Redirection:	5
Max Auth:	2	SIP User Agent Name:	\$VERSION
SIP Server Name:	\$VERSION	SIP Reg User Agent Name:	
SIP Accept Language:		DTMF Relay MIME Type:	application/dtmf-relay
Remove Last Reg:	no	Use Compact Header:	no
Escape Display Name:	no	Linksys Key System:	no
SIP-B Enable:	no	Talk Package:	no
Hold Package:	no	Conference Package:	no
Notify Conference:	no		

SIP Timer Values (sec)

SIP T1:	.5	SIP T2:	4
SIP T4:	5	SIP Timer B:	16
SIP Timer F:	16	SIP Timer H:	16
SIP Timer D:	16	SIP Timer J:	16
INVITE Expires:	240	ReINVITE Expires:	30
Reg Min Expires:	1	Reg Max Expires:	7200
Reg Retry Intvl:	30	Reg Retry Long Intvl:	1200
Sub Min Expires:	10	Sub Max Expires:	7200
Sub Retry Intvl:	10		

Response Status Code Handling

SIT1 RSC:		SIT2 RSC:	
SIT3 RSC:		SIT4 RSC:	
Try Backup RSC:		Retry Reg RSC:	

RTP Parameters

RTP Port Min:	7000	RTP Port Max:	65000
RTP Packet Size:	0.030	Max RTP ICMP Err:	0
RTCP Tx Interval:	0	No UDP Checksum:	no
Symmetric RTP:	no	Stats In BYE:	no

SDP Payload Types

AVT Dynamic Payload:	101	INFOREQ Dynamic Payload:	
G726r16 Dynamic Payload:	98	G726r24 Dynamic Payload:	97
G726r40 Dynamic Payload:	96	G729b Dynamic Payload:	99
AVT Codec Name:	telephone-event	G711u Codec Name:	PCMU
G711a Codec Name:	PCMA	G726r16 Codec Name:	G726-16
G726r24 Codec Name:	G726-24	G726r32 Codec Name:	G726-32
G726r40 Codec Name:	G726-40	G729a Codec Name:	G729a
G729b Codec Name:	G729ab	G723 Codec Name:	G723

Internet

Sipura SPA Configuration - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Search Favorites

Address http://192.168.1.65/admin/advanced Go Links

Info System SIP Provisioning Regional **Phone** Ext 1 Ext 2 User

User Login basic | advanced
Personal Directory Call History

General

Station Name: XeloQ Sales Voice Mail Number:

Text Logo:

Line Key 1

Extension: 1 Short Name:

Share Call Appearance: private

Line Key 2

Extension: 1 Short Name:

Share Call Appearance: private

Line Key 3

Extension: 1 Short Name:

Share Call Appearance: private

Line Key 4

Extension: 1 Short Name:

Share Call Appearance: private

Line Key LED Pattern

Idle LED:		Remote Undefined LED:	
Local Seized LED:		Remote Seized LED:	
Local Progressing LED:		Remote Progressing LED:	
Local Ringing LED:		Remote Ringing LED:	
Local Active LED:		Remote Active LED:	
Local Held LED:		Remote Held LED:	
Register Failed LED:		Disabled LED:	
Registering LED:		Call Back Active LED:	

Supplementary Services

Conference Serv:	yes	Attn Transfer Serv:	yes
Blind Transfer Serv:	yes	DND Serv:	yes
Block ANC Serv:	yes	Call Back Serv:	yes
Block CID Serv:	yes	Secure Call Serv:	yes
Cfwd All Serv:	yes	Cfwd Busy Serv:	yes
Cfwd No Ans Serv:	yes	Paging Serv:	yes
Call Park Serv:	yes	Call Pick Up Serv:	yes
ACD Login Serv:	no	Group Call Pick Up Serv:	yes
ACD Ext:	1		

Ring Tone

Internet

Sipura SPA Configuration - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Search Favorites

Address http://192.168.1.65/admin/advanced Go Links

Info System SIP Provisioning Regional Phone **Ext 1** Ext 2 User

User Login basic | advanced
Personal Directory Call History

General

Line Enable: yes

Share Line Appearance

Share Ext: private Shared User ID:

Subscription Expires: 3600

NAT Settings

NAT Mapping Enable: no NAT Keep Alive Enable: yes

NAT Keep Alive Msg: \$NOTIFY NAT Keep Alive Dest: \$PROXY

Network Settings

SIP TOS/DiffServ Value: 0x68 SIP CoS Value: 3

RTP TOS/DiffServ Value: 0xb8 RTP CoS Value: 6

Network Jitter Level: high Jitter Buffer Adjustment: up and down

SIP Settings

SIP Port: 5060 SIP 100REL Enable: no

EXT SIP Port: Auth Resync-Reboot: yes

SIP Proxy-Require: SIP Remote-Party-ID: no

Referor Bye Delay: 4 Refer-To Target Contact: yes

Referee Bye Delay: 0 SIP Debug Option: none

Refer Target Bye Delay: 0 Sticky 183: no

Call Feature Settings

Blind Attn-Xfer Enable: no MOH Server:

Message Waiting: no Auth Page: no

Default Ring: 1 Auth Page Realm:

Conference Bridge URL: Auth Page Password:

Mailbox ID: Voice Mail Server:

State Agent: CFWD Notify Serv: no

CFWD Notifier:

Proxy and Registration

Proxy: sip.goandcall.com Use Outbound Proxy: yes

Outbound Proxy: sip.goandcall.com:6060 Use OB Proxy In Dialog: yes

Register: yes Make Call Without Reg: no

Register Expires: 3600 Ans Call Without Reg: no

Use DNS SRV: no DNS SRV Auto Prefix: no

Proxy Fallback Intvl: 3600 Proxy Redundancy Method: Normal

Internet

Sipura SPA Configuration - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Search Favorites

Address <http://192.168.1.65/admin/advanced> Go Links

Subscriber Information

Display Name:	<input type="text" value="XeloQ Sales"/>	User ID:	<input type="text" value="700200"/>
Password:	<input type="password" value="*****"/>	Use Auth ID:	<input type="text" value="no"/>
Auth ID:	<input type="text"/>		
Mini Certificate:	<input type="text"/>		
SRTP Private Key:	<input type="text"/>		

Audio Configuration

Preferred Codec:	<input type="text" value="G729a"/>	Use Pref Codec Only:	<input type="text" value="no"/>
G729a Enable:	<input type="text" value="yes"/>	G723 Enable:	<input type="text" value="yes"/>
G726-16 Enable:	<input type="text" value="no"/>	G726-24 Enable:	<input type="text" value="no"/>
G726-32 Enable:	<input type="text" value="no"/>	G726-40 Enable:	<input type="text" value="no"/>
Release Unused Codec:	<input type="text" value="yes"/>	DTMF Process AVT:	<input type="text" value="yes"/>
Silence Supp Enable:	<input type="text" value="no"/>	DTMF Tx Method:	<input type="text" value="Auto"/>

Dial Plan

Dial Plan:	<input type="text" value="(*xx [3469]11 0 00 [2-9]xxxxxx 1xxx[2-9]xxxxxxS0 xxxxxxxxxxxxx.)"/>
Enable IP Dialing:	<input type="text" value="yes"/>

[User Login](#) [basic](#) | [advanced](#)

Internet