

## Configuration LinkSys SPA-941 on XeloQ Communications / Goandcall.com

Sipura SPA Configuration - Microsoft Internet Explorer

Address <http://192.168.1.65/admin/advanced>



technology, inc.

### Sipura Telephone Configuration

Info **System** SIP Provisioning Regional Phone Ext 1 Ext 2 User Sipura Technology Inc [User Login](#) [basic](#) | [advanced](#)  
[Personal Directory](#) [Call History](#)

#### System Configuration

Restricted Access Domains:	<input type="text"/>		
Enable Web Server:	<input type="text" value="yes"/>	Web Server Port:	<input type="text" value="80"/>
Enable Web Admin Access:	<input type="text" value="yes"/>	Admin Passwd:	<input type="text"/>
User Password:	<input type="text"/>		

#### Internet Connection Type

DHCP:	<input type="text" value="yes"/>		
Static IP:	<input type="text"/>	NetMask:	<input type="text"/>
Gateway:	<input type="text"/>		

#### Optional Network Configuration

HostName:	<input type="text"/>	Domain:	<input type="text"/>
Primary DNS:	<input type="text" value="81.26.212.151"/>	Secondary DNS:	<input type="text" value="195.121.1.34"/>
DNS Server Order:	<input type="text" value="Manual"/>	DNS Query Mode:	<input type="text" value="Sequential"/>
Syslog Server:	<input type="text"/>		
Debug Level:	<input type="text" value="0"/>	Debug Server:	<input type="text"/>
Secondary NTP Server:	<input type="text"/>		
Primary NTP Server:	<input type="text"/>		

#### VLAN Settings

Enable VLAN:	<input type="text" value="no"/>	VLAN ID:	<input type="text" value="1"/>
--------------	---------------------------------	----------	--------------------------------

[User Login](#) [basic](#) | [advanced](#)

Copyright © 2003-2005 Sipura Technology. All Rights Reserved.

<http://www.sipura.com/> Internet

DNS 1: use 81.26.212.151 (is a goandcall.com DNS server; use only if normal DNS is not accurate)

Sipura SPA Configuration - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Search Favorites

Address http://192.168.1.65/admin/advanced Go Links

Info System **SIP** Provisioning Regional Phone Ext 1 Ext 2 User

User Login basic | advanced  
Personal Directory Call History

### SIP Parameters

Max Forward:	70	Max Redirection:	5
Max Auth:	2	SIP User Agent Name:	\$VERSION
SIP Server Name:	\$VERSION	SIP Reg User Agent Name:	
SIP Accept Language:		DTMF Relay MIME Type:	application/dtmf-relay
Remove Last Reg:	no	Use Compact Header:	no
Escape Display Name:	no	Linksys Key System:	no
SIP-B Enable:	no	Talk Package:	no
Hold Package:	no	Conference Package:	no
Notify Conference:	no		

### SIP Timer Values (sec)

SIP T1:	.5	SIP T2:	4
SIP T4:	5	SIP Timer B:	16
SIP Timer F:	16	SIP Timer H:	16
SIP Timer D:	16	SIP Timer J:	16
INVITE Expires:	240	ReINVITE Expires:	30
Reg Min Expires:	1	Reg Max Expires:	7200
Reg Retry Intvl:	30	Reg Retry Long Intvl:	1200
Sub Min Expires:	10	Sub Max Expires:	7200
Sub Retry Intvl:	10		

### Response Status Code Handling

SIT1 RSC:		SIT2 RSC:	
SIT3 RSC:		SIT4 RSC:	
Try Backup RSC:		Retry Reg RSC:	

### RTP Parameters

RTP Port Min:	7000	RTP Port Max:	65000
RTP Packet Size:	0.030	Max RTP ICMP Err:	0
RTCP Tx Interval:	0	No UDP Checksum:	no
Symmetric RTP:	no	Stats In BYE:	no

### SDP Payload Types

AVT Dynamic Payload:	101	INFOREQ Dynamic Payload:	
G726r16 Dynamic Payload:	98	G726r24 Dynamic Payload:	97
G726r40 Dynamic Payload:	96	G729b Dynamic Payload:	99
AVT Codec Name:	telephone-event	G711u Codec Name:	PCMU
G711a Codec Name:	PCMA	G726r16 Codec Name:	G726-16
G726r24 Codec Name:	G726-24	G726r32 Codec Name:	G726-32
G726r40 Codec Name:	G726-40	G729a Codec Name:	G729a
G729b Codec Name:	G729ab	G723 Codec Name:	G723

Internet

Sipura SPA Configuration - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Search Favorites

Address http://192.168.1.65/admin/advanced Go Links

Info System SIP Provisioning Regional **Phone** Ext 1 Ext 2 User

User Login basic | advanced  
Personal Directory Call History

**General**

Station Name: XeloQ Sales Voice Mail Number:

Text Logo:

**Line Key 1**

Extension: 1 Short Name:

Share Call Appearance: private

**Line Key 2**

Extension: 1 Short Name:

Share Call Appearance: private

**Line Key 3**

Extension: 1 Short Name:

Share Call Appearance: private

**Line Key 4**

Extension: 1 Short Name:

Share Call Appearance: private

**Line Key LED Pattern**

Idle LED: Remote Undefined LED:

Local Seized LED: Remote Seized LED:

Local Progressing LED: Remote Progressing LED:

Local Ringing LED: Remote Ringing LED:

Local Active LED: Remote Active LED:

Local Held LED: Remote Held LED:

Register Failed LED: Disabled LED:

Registering LED: Call Back Active LED:

**Supplementary Services**

Conference Serv: yes Attn Transfer Serv: yes

Blind Transfer Serv: yes DND Serv: yes

Block ANC Serv: yes Call Back Serv: yes

Block CID Serv: yes Secure Call Serv: yes

Cfwd All Serv: yes Cfdw Busy Serv: yes

Cfwd No Ans Serv: yes Paging Serv: yes

Call Park Serv: yes Call Pick Up Serv: yes

ACD Login Serv: no Group Call Pick Up Serv: yes

ACD Ext: 1

**Ring Tone**

Internet

Sipura SPA Configuration - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Refresh Home Search Favorites

Address <http://192.168.1.65/admin/advanced> Go Links

Info System SIP Provisioning Regional Phone **Ext 1** Ext 2 User

[User Login](#) [basic](#) | [advanced](#)  
[Personal Directory](#) [Call History](#)

**General**  
Line Enable:

**Share Line Appearance**  
Share Ext:  Shared User ID:   
Subscription Expires:

**NAT Settings**  
NAT Mapping Enable:  NAT Keep Alive Enable:   
NAT Keep Alive Msg:  NAT Keep Alive Dest:

**Network Settings**  
SIP TOS/DiffServ Value:  SIP CoS Value:   
RTP TOS/DiffServ Value:  RTP CoS Value:   
Network Jitter Level:  Jitter Buffer Adjustment:

**SIP Settings**  
SIP Port:  SIP 100REL Enable:   
EXT SIP Port:  Auth Resync-Reboot:   
SIP Proxy-Require:  SIP Remote-Party-ID:   
Referor Bye Delay:  Refer-To Target Contact:   
Referee Bye Delay:  SIP Debug Option:   
Refer Target Bye Delay:  Sticky 183:

**Call Feature Settings**  
Blind Attn-Xfer Enable:  MOH Server:   
Message Waiting:  Auth Page:   
Default Ring:  Auth Page Realm:   
Conference Bridge URL:  Auth Page Password:   
Mailbox ID:  Voice Mail Server:   
State Agent:  CFWD Notify Serv:   
CFWD Notifier:

**Proxy and Registration**  
Proxy:  Use Outbound Proxy:   
Outbound Proxy:  Use OB Proxy In Dialog:   
Register:  Make Call Without Reg:   
Register Expires:  Ans Call Without Reg:   
Use DNS SRV:  DNS SRV Auto Prefix:   
Proxy Fallback Intvl:  Proxy Redundancy Method:

Internet

Sipura SPA Configuration - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Search Favorites

Address <http://192.168.1.65/admin/advanced> Go Links

### Subscriber Information

Display Name:	<input type="text" value="XeloQ Sales"/>	User ID:	<input type="text" value="700200"/>
Password:	<input type="password" value="*****"/>	Use Auth ID:	<input type="text" value="no"/>
Auth ID:	<input type="text"/>		
Mini Certificate:	<input type="text"/>		
SRTP Private Key:	<input type="text"/>		

### Audio Configuration

Preferred Codec:	<input type="text" value="G729a"/>	Use Pref Codec Only:	<input type="text" value="no"/>
G729a Enable:	<input type="text" value="yes"/>	G723 Enable:	<input type="text" value="yes"/>
G726-16 Enable:	<input type="text" value="no"/>	G726-24 Enable:	<input type="text" value="no"/>
G726-32 Enable:	<input type="text" value="no"/>	G726-40 Enable:	<input type="text" value="no"/>
Release Unused Codec:	<input type="text" value="yes"/>	DTMF Process AVT:	<input type="text" value="yes"/>
Silence Supp Enable:	<input type="text" value="no"/>	DTMF Tx Method:	<input type="text" value="Auto"/>

### Dial Plan

Dial Plan:	<input type="text" value="(*xx [3469]11 0 00 [2-9]xxxxxx 1xxx[2-9]xxxxxxS0 xxxxxxxxxxxxx.)"/>
Enable IP Dialing:	<input type="text" value="yes"/>

[User Login](#) [basic](#) | [advanced](#)

Internet